

03.2.300

7

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicant: Charles Grasso; Monte Pearson; Robert S. Creager  
Docket: 99-056-TAP  
Title: METHOD AND SYSTEM FOR EMISSION SUPPRESSION IN DETECTION OF DATA CARTRIDGE LABEL

CERTIFICATE UNDER 37 CFR 1.10

'Express Mail' mailing label number: EL370106770US

Date of Deposit **March 22, 2000**

I hereby certify that this paper or fee is being deposited with the United States Postal Service 'Express Mail Post Office To Addressee' service under 37 CFR 1.10 and is addressed to the Assistant Commissioner for Patents, Washington, D.C. 20231.

By: *Stephanie Klepp*  
Name: Stephanie Klepp

BOX PATENT APPLICATION  
Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

We are transmitting herewith the attached:

- ☒ Transmittal sheet, in duplicate, containing Certificate under 37 CFR 1.10.
- ☒ Utility Patent Application: Spec. 7 pgs; 5 claims; Abstract 1 pgs.  
The fee has been calculated as shown below in the 'Claims as Filed' table.
- ☒ 3 sheets formal drawings
- ☒ A signed Combined Declaration and Power of Attorney
- ☒ Assignment of the invention to Storage Technology Corporation, Recordation Form Cover Sheet
- ☒ Please use deposit account #19-4545 for all filing fees relating to this patent application.
- ☒ Return postcard

CLAIMS AS FILED

Number of Claims Filed		In Excess of:		Number Extra		Rate		Fee
Basic Filing Fee								\$690.00
Total Claims								
18	-	20	=	0	x	0.00	=	\$0.00
Independent Claims								
4	-	3	=	1	x	78.00	=	\$78.00
MULTIPLE DEPENDENT CLAIM FEE								\$0.00
TOTAL FILING FEE								\$768.00

Please charge any additional fees or credit overpayment to Deposit Account No. 19-4545. A duplicate of this sheet is enclosed.

Storage Technology Corporation  
One StorageTek Drive  
Mail stop 4309  
Louisville, CO 80028-4309

By: *Timothy R. Schulte*  
Name: Timothy R. Schulte  
Reg. No.: 29,013  
Initials: TRS

**METHOD AND SYSTEM FOR EMISSION SUPPRESSION  
IN DETECTION OF DATA CARTRIDGE LABELS**

**Background of the Invention**

5     1.     Field of the Invention

        The present invention relates generally to data storage subsystems, and more particularly to a robotic system and method for identifying data cartridge locations with reduced electromagnetic emissions in a data cartridge library system.

10     2.     Description of Related Art

        A typical digital data cartridge handling library includes number of columns of stacked bins containing data cartridges positioned around a centrally located manipulating arm with a cartridge grasping hand which can rotate, translate and elevate to position the hand in front of a particular bin containing the desired cartridge. The arrangement is sometimes called a "silo" arrangement, borrowing a term from the farming industry. The data cartridges may be optical data disks, tape cartridges or magnetic disc cartridges, depending on the type of recording apparatus involved. Typically, the data cartridges are data tape cartridges and the drive is a tape drive.

        When the manipulating arm is properly positioned opposite a desired bin or cartridge slot in the desired column, the arm automatically extends and the hand grips the cartridge. The arm retracts, pulling the cartridge out of the bin. The arm then rotates, elevates, and moves the hand in or out to position the gripped cartridge into a cartridge drive apparatus such as a tape drive so that the data on the cartridge may be read or appropriately changed as required by the host computer system.

        When the operations requiring the cartridge to be in the drive are completed, the host computer then directs the manipulating arm to replace the cartridge in its assigned bin and then proceed with obtaining a next cartridge, if needed.

A CCD camera located on the hand periodically senses the location of the hand in order to precisely position the hand and provide location information feedback to the manipulator controller. This camera also has a linear array of LEDs arranged to project a line of red light to illuminate the tape cartridge bin markers as well as the identifying bar code labels on the cartridges. Since the LEDs and the camera are typically maintained on at all times, much of the electronics circuitry for camera control and signal processing is mounted on the hand with the camera. This component mass must be elevated, translated and rotated as part of the robot manipulator apparatus.

One of the byproducts of these data cartridge handling libraries is the production of unwanted noise. This noise, in particular, includes electromagnetic radiation (EMR) noise which can adversely affect other components and/or systems located nearby, such as peripheral devices, computers, video monitors, etc. Consequently, the cartridge libraries are typically shielded to prevent escape of the EMR or at least minimize the transmission of EMR.

One of the prime sources of unwanted EMR in these library systems originates with the electronic components located on the hand itself. Therefore significant amounts of material are utilized on the hand to effectively shield the surrounding environment from the EMR. This increases the size and mass of the hand and therefore the manipulator arm strength and mass must be appropriately sized in order to overcome inertial forces and produce the desired movements in the desired time periods in order to optimally minimize the time required for a "pick" or "put" operation to be performed. It is with respect to these and other considerations that the present invention has been made.

### **Summary of the Invention**

The present invention is a system and method for use in a data cartridge handling library for reducing the emissions of electromagnetic radiation (EMR) from the data cartridge handling library. The method basically involves turning on the positioning camera located on the manipulator hand in the library silo only when an anticipated desired bin location is approached during an audit operation.

More particularly, the method in accordance with the present invention comprises storing cartridges in tape handling library storage bins, turning on the manipulator camera, performing an audit of all of the cartridges in the storage bins with the manipulator hand, storing the bin location coordinates for each bin containing a cartridge along with cartridge identification data in a database, turning off the camera, and subsequently retrieving cartridges from the bins by utilizing the bin location coordinates.

These and various other features as well as advantages which characterize the present invention will be apparent from a reading of the following detailed description and a review of the associated drawings.

### **Brief Description of the Drawings**

Fig. 1 is a schematic representation of a cartridge library system including a host computer, data cartridge storage silo and a storage controller in accordance with a preferred embodiment of the present invention.

Fig. 2 is a block diagram of the hand manipulator storage controller microprocessors in one preferred embodiment of the present invention.

Fig. 3 is a process flow diagram of operations of the audit software routine in the preferred embodiment of the present invention shown in Fig. 2.

### **Detailed Description of the Preferred Embodiment**

FIG. 1 depicts an automated cartridge library system **100**. Operation of automated cartridge library system **100** is directed by a host computer **102**. Host computer **102** communicates with a library control unit (LCU) **112**. The operation of a robot arm **106** within a library storage module (LSM) **108** is governed by the library control unit (LCU) **112** which interprets signals from host computer **102** and provides appropriate signals to the robot manipulator arm **106** to control its motion and operation. Signals from host computer **102** control the handling and storage of tape cartridges within the library storage module **108**. Signals between host computer **102** and the library storage module **108** are conducted over conductors which are represented by the solid lines in FIG. 1. Data to be written to a tape cartridge (not

shown in FIG. 1) or read from a tape cartridge is communicated over data lines, represented by the dotted lines of FIG. 1, through the tape control unit (TCU) 110. TCU 110 controls the operation of each of the tape drives 104 associated with LSM 108.

5 In general terms, when there is a need to read data from a tape cartridge in LSM 108, robot arm 106, in response to signals from the host computer 102, retrieves the appropriate tape cartridge from a storage cell and inserts the tape cartridge in a tape drive 104. Signals from host computer 102 through the TCU 110 then control the reading/writing of data from/to the tape cartridge.

10 As shown in block diagram form in Fig. 2, the library control unit (LCU) 112 which controls the robot manipulator arm 106 has a main microprocessor 202. The robot arm 106 has a robot manipulator hand microprocessor 204 and a camera imager microprocessor 206, the latter two of which are physically located on the gripper hand of the robot arm 106.

15 The main processor 202 provides a camera enable signal to the crystal oscillator 210 in the hand microprocessor 204. When enabled, the crystal oscillator 210 provides a clock input to the camera clock generator 212. The camera clock generator 212 in turn provides clock input and output signals 214 to the camera imager 216 in the camera imager microprocessor 206. The main processor 202 also provides image exposure control, picture synchronization and pixel synchronization signals to the clock generator 212 via lines 218, 220 and 222 respectively. When the camera clock generator 212 is turned on, the camera imager microprocessor 206 starts the camera and analog output signals are passed from the camera imager 206 via line 224 to a sample/hold circuit 226 and thence through buffers to  
20 the main computer microprocessor 202 via lines 228.

25 Microprocessor 202 stores library cartridge identification data and position information in a database which may be located in the LCU 112. In order to accurately position the hand of the manipulator arm 106 to retrieve a cartridge or place a cartridge in a particular bin, the LCU 104 must have accurate location  
30 information as well as cartridge identification information. This information is gathered initially through a software "Audit Subsystem" routine which reads and catalogues each and every bin location and its contents into the database in the

LCU **112**. This database is subsequently utilized by the LCU **112** to control the operation of the robot arm **106** during normal cartridge retrieval operations.

During the initial information gathering operation, or performance of the Audit Subsystem **303**, the robot manipulator **106** systematically drives to anticipated bin location and reads picture information identifying the exact bin location with the hand camera. The content of each bin is also read with the manipulator hand camera and associated with the location. This data is then stored for subsequent tape cartridge handling operations without the use of the hand camera.

Typically, the stored information only is utilized to place and retrieve cartridges from and to the bins without the aid of the robot manipulator hand camera. However, periodically, and whenever cartridge changes are made, the Audit Subsystem routine is invoked in order to add data to the database and/or verify the accuracy of hand manipulation or travel. Thus, during normal operation, the camera located on the manipulator arm is off and not used, thus minimizing any EMR emissions from the library.

Referring now to Fig. **3**, a flow diagram of the operational software steps in the Audit subsystem **300** is shown. The LCU **112** triggers the virtual Audit Subsystem **300** when tape cartridges are added or replaced, and periodically to verify the accuracy of hand operation. The virtual Audit Subsystem **300** transfers control to operation **301** where the Database is queried. If the Tape Label data is known then the Cell Contents Database **302** is returned to the LCU **112**. IF the Tape Label Data is not known then the Audit Subsystem **303** is called. When the Audit subsystem **303** is called, a request for a picture is issued on line **305** to the line scan camera software interface **304**. Control then transfers to operation **310** where the state of the camera is queried. If the camera is on, control transfers to operation **312** which provides a delay until the picture gathered is complete. The camera interface **304** then transfers control to operation **306** where data is accumulated for the picture. When sufficient data is accumulated, control transfers to operation **308** where the picture data is registered. When the picture is complete, control transfers back to the Line Scan Camera Software Interface operation **304** and thence via line **313** to the Audit subsystem **303** and the Tape Label Data is written to the Cell Contents Database **317**.

If the camera is not on in query operation **310**, control transfers to operation **314** where the camera is turned on. A Request for a Picture turns on the Camera Enable **208** to start the camera and its associated clocking. Control remains in operation **314** until a camera saturation condition is cleared, at which time control  
5 transfers to operation **312** as discussed in the previous paragraph. When the Label Data is known and there are no more requests for pictures the Line Scan Camera Software Interface **304** turns off the camera and its associated clocking.

The audit subroutine **303** described above is typically only invoked when the system is reset or upon opening or closing the doors into the unit. Otherwise the  
10 audit subroutine is invoked only when an error condition is detected such as cells being unexpectedly full or empty or the Get/Put call system stalls.

The above specification, examples and data provide a complete description of one embodiment of the method and the apparatus of the invention. Many variations of the invention will be readily apparent to those skilled in the art. Since many  
15 embodiments of the invention can be made without departing from the spirit and scope of the invention, all such modifications and variations are envisioned as being within the scope of the invention as defined by the following claims.

## Claims

What is claimed is:

1. A data cartridge handling system comprising:

a data cartridge storage array having a plurality of bins each for removably  
5 receiving and storing a data cartridge;

a robotic manipulator operatively positioned for selectively retrieving data  
cartridges from the bins, transferring the retrieved data cartridges to and from a data  
reading and recording device and replacing data cartridges into the bins in  
accordance with instructions received from a control system operatively coupled to  
10 the robotic manipulator for directing movement of the manipulator, the manipulator  
including a grasping hand for grasping a selected data cartridge and moving the  
data cartridge in and out of a bin and a camera mounted on the hand for sensing the  
location of the hand with reference to each of the plurality of bins, wherein the  
camera is operated during an audit operation initiated by the control system to  
15 provide bin location data to a memory subsequently utilized by the control system to  
position the grasping hand of the robotic manipulator.

2. A data cartridge handling system as defined in claim 1 wherein the  
camera is utilized only during the audit operation.

3. A system as defined in claim 2 wherein the camera includes an  
oscillator located on the hand whose output is selectively provided to the camera  
only during an audit operation.

4. A system as defined in claim 1 wherein the camera further provides  
cartridge identification data to the memory to provide a map of bin location and bin  
content.

5. A system as defined in claim 4 wherein manipulator positioning is only  
controlled by the camera during an audit operation.



6. A system as defined in claim 1 wherein the control system routinely directs movement of the robotic manipulator utilizing location data from the memory and operates the camera only during an audit operation.

7. A system as defined in claim 1 further comprising an oscillator whose output is selectively provided to the camera on the hand only during an audit operation.

8. A data cartridge handling library apparatus having reduced electromagnetic radiation emissions comprising:

a plurality of data cartridge storage bins arranged around a robotic manipulator for retrieving and replacing cartridges from and to the bins;

5 a camera mounted on the manipulator for sensing a position of the manipulator with respect to the plurality of data cartridge storage bins, the camera being operable during an audit operation to identify each bin location;

10 a manipulator control system operatively coupled to the robotic manipulator for selectively controlling movement of the manipulator and operating the camera to sense and record manipulator position information at each bin location and store position and bin location information in a memory accessible by the manipulator control.

9. The apparatus according to claim 8 system wherein the control system performs data cartridge storage and retrieval operations utilizing the bin location and manipulator position information stored in the memory to position the manipulator.

10. The apparatus according to claim 8 wherein the manipulator comprises a grasping hand having the camera mounted thereon.

11. The apparatus according to claim 10 wherein an oscillator mounted on the hand has an output enabled to operate the camera during an audit operation.

12. The apparatus according to claim 8 further comprising a grasping hand on the manipulator having the camera mounted thereon, the camera having an oscillator having an output enabled by the control system, wherein the control system disables the output of the oscillator and performs data cartridge storage and

5 retrieval operations utilizing the bin location and manipulator position information stored in the memory during normal library operations.

13. The apparatus according to claim 12 wherein the oscillator output is enabled only during an audit operation by the manipulator control system.

14. A method for reducing electromagnetic radiation emissions from a data cartridge handling library apparatus comprising the steps of:

providing a plurality of data cartridge storage bins arranged around a robotic manipulator for retrieving and replacing cartridges from and to the bins

5 providing a manipulator control system operatively coupled to the robotic manipulator for selectively controlling movement of the manipulator;

providing a camera mounted on the manipulator for sensing a position of the manipulator with respect to the plurality of data cartridge storage bins;

turning on the camera;

10 performing an audit operation using the camera to identify each bin location, record manipulator position information at each bin location and store bin location information in a memory accessible by the manipulator control system;

turning the camera off;

performing subsequent data cartridge storage and retrieval operations

15 utilizing the bin location and manipulator position information stored in the memory to position the manipulator.

15. A method as defined in claim 14 wherein the manipulator comprises a grasping hand having the camera mounted thereon and the step of turning on the camera includes the step of enabling an output of an oscillator mounted on the hand.

16. The method as defined in claim 15 wherein the step of turning off the camera includes disabling the output of the oscillator mounted on the hand.

17. A method for reducing electromagnetic radiation emissions from a data cartridge handling library apparatus comprising the steps of:

providing a plurality of data cartridge storage bins arranged around a robotic

manipulator for retrieving and replacing cartridges from and to the bins

- 5            providing a manipulator control system operatively coupled to the robotic  
manipulator for selectively controlling movement of the manipulator;  
             providing a camera mounted on the manipulator for sensing a position of the  
manipulator with respect to the plurality of data cartridge storage bins;  
             operating the camera during an audit operation to identify a bin location,  
10        record manipulator position information at the bin location and store bin location  
information in a memory accessible by the manipulator control system.

18.        The method according to claim 17 further comprising the step of:  
             performing data cartridge storage and retrieval operations utilizing the bin  
location and manipulator position information stored in the memory to position the  
manipulator.


# METHOD AND SYSTEM FOR EMISSION SUPPRESSION

## IN DETECTION OF DATA CARTRIDGE LABELS

### Abstract

5 A system and method for minimizing electromagnetic radiation emissions from a data cartridge handling library employs intermittent operation of the video camera to ascertain correct bin locations and verify automated access between bin locations. This intermittent operation is utilized when an error is suspected or upon a predetermined routine to verify manipulation accuracy.

**FIG. 1**







Fig. 2



**Figure 3**

STORAGE TECHNOLOGY CORPORATION  
United States Patent Application

**COMBINED DECLARATION AND POWER OF ATTORNEY**

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name. I believe I am an original, first and joint inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled: METHOD AND SYSTEM FOR EMISSION SUPPRESSION IN DETECTION OF DATA CARTRIDGE LABELS.

the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, § 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior Foreign Application(s)			Priority Claimed?
(Number)	(Country)	(Day/Month/Year Filed)	<input type="checkbox"/> Yes <input type="checkbox"/> No
(Number)	(Country)	(Day/Month/Year Filed)	<input type="checkbox"/> Yes <input type="checkbox"/> No

I hereby claim the benefit under Title 35, United States Code, § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, § 112, I acknowledge the duty to disclose information which is material to patentability as defined in Title 37, Code of Federal Regulations, § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application.

(Application Number)	(Filing Date)	(Status - patented, pending abandoned)
----------------------	---------------	--

(Application Number)	(Filing Date)	(Status - patented, pending abandoned)
----------------------	---------------	--

I hereby appoint the following attorney(s) and/or agent(s) to prosecute this application and to transact all business in the U.S. Patent and Trademark Office connected therewith:


Schulte, Timothy R.	Reg. No. 29,013	Bailey, Wayne P.	Reg. No. 34,289
---------------------	-----------------	------------------	-----------------





Albrecht, John W.	Reg. No. 40,481	Kowalchyk, Alan W.	Reg. No. 31,535
Anderson, Gregg I.	Reg. No. 28,828	Kowalchyk, Katherine M.	Reg. No. 36,848
Ansems, Gregory M.	Reg. No. 42,264	Lacy, Paul E.	Reg. No. 38,946
Batzli, Brian H.	Reg. No. 32,960	Larson, James A.	Reg. No. 40,443
Beard, John L.	Reg. No. 27,612	Liepa, Mara E.	Reg. No. 40,066
Black, Bruce E.	Reg. No. 41,622	Lindquist, Timothy A.	Reg. No. 40,701
Bruess, Steven C.	Reg. No. 34,130	McDonald, Daniel W.	Reg. No. 32,044
Byrne, Linda M.	Reg. No. 32,404	McIntyre, Iain A.	Reg. No. 40,337
Carlson, Alan G.	Reg. No. 25,959	Mueller, Douglas P.	Reg. No. 30,300
Caspers, Philip P.	Reg. No. 33,227	Pauly, Daniel M.	Reg. No. 40,123
Chiapetta, James R.	Reg. No. 39,634	Phillips, John B.	Reg. No. 37,206
Clifford, John A.	Reg. No. 30,247	Plunkett, Theodore	Reg. No. 37,209
Cochran, William W.	Reg. No. 26,652	Pytel, Melissa J.	Reg. No. 41,512
Daignault, Ronald A.	Reg. No. 25,968	Reich, John C.	Reg. No. 37,703
Daley, Dennis R.	Reg. No. 34,994	Reiland, Earl D.	Reg. No. 25,767
Dalglish, Leslie E.	Reg. No. 40,579	Schmaltz, David G.	Reg. No. 39,828
Daulton, Julie R.	Reg. No. 36,414	Schuman, Mark D.	Reg. No. 31,197
Devries Smith, Katherine M.	Reg. No. 42,157	Schumann, Michael D.	Reg. No. 30,422
DiPietro, Mark J.	Reg. No. 28,707	Scull, Timothy B.	Reg. No. 42,137
Edell, Robert T.	Reg. No. 20,187	Sebald, Gregory A.	Reg. No. 33,280
Epp Ryan, Sandra	Reg. No. 39,667	Skoog, Mark T.	Reg. No. 40,178
Glance, Robert J.	Reg. No. 40,620	Soderberg, Richard	Reg. No. P43,352
Goggin, Matthew J.	Reg. No. 44,125	Storer, Shelley D.	Reg. No. P45,135
Golla, Charles E.	Reg. No. 26,896	Sumner, John P.	Reg. No. 29,114
Gorman, Alan G.	Reg. No. 38,472	Sumners, John S.	Reg. No. 24,216
Gould, John D.	Reg. No. 18,223	Swenson, Erik G.	Reg. No. P45,147
Gregson, Richard	Reg. No. 41,804	Tellekson, David K.	Reg. No. 32,314
Gresens, John J.	Reg. No. 33,112	Trembath, Jon R.	Reg. No. 38,344
Hamre, Curtis B.	Reg. No. 29,165	Underhill, Albert L.	Reg. No. 27,403
Hillson, Randall A.	Reg. No. 31,838	Vandenburgh, J. Derek	Reg. No. 32,179
Holzer, Jr., Richard J.	Reg. No. 42,668	Wahl, John R.	Reg. No. 33,044
Johnston, Scott W.	Reg. No. 39,721	Welter, Paul A.	Reg. No. 20,890
Kadievitch, Natalie D.	Reg. No. 34,196	Whipps, Brian	Reg. No. 43,261
Kastelic, Joseph M.	Reg. No. 37,160	Wickhem, J. Scot	Reg. No. 41,376
Kettelberger, Denise	Reg. No. 33,924	Williams, Douglas J.	Reg. No. 27,054
Keys, Jeramie J.	Reg. No. 42,724	Witt, Jonelle	Reg. No. 41,980
Knearl, Homer L.	Reg. No. 21,197	Xu, Min S.	Reg. No. 39,536
Stoll-Debell, Kirstin L.	Reg. No. 43,164	Zeuli, Anthony R.	Reg. No. P-45,255
Prendergast, Paul J.	Reg. No. P-46,068		

Address all telephone calls to Wayne P. Bailey at Telephone No. (303) 673-8223 and address all correspondence to Timothy R. Schulte and Wayne P. Bailey, Storage Technology Corporation, MS 4309, One StorageTek Drive, Louisville, Colorado 80028-4309.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> Grasso	<b>First Given Name</b> Charles	<b>Second Given Name</b>
0	<b>Residence &amp; Citizenship</b>	<b>City</b> Louisville	<b>State or Foreign Country</b> Colorado	<b>Country of Citizenship</b> USA
1	<b>Post Office Address</b>	<b>Post Office Address</b> 479 Grouse Court	<b>City</b> Louisville	<b>State &amp; Zip Code/Country</b> Colorado 80027/USA
<b>Signature of Inventor 201:</b> 				<b>Date:</b> 3-7-00

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> Pearson	<b>First Given Name</b> Monte	<b>Second Given Name</b>
0	<b>Residence &amp; Citizenship</b>	<b>City</b> Westminster	<b>State or Foreign Country</b> Colorado	<b>Country of Citizenship</b> USA
2	<b>Post Office Address</b>	<b>Post Office Address</b> 10042 W. 100 <sup>th</sup> Place	<b>City</b> Westminster	<b>State &amp; Zip Code/Country</b> Colorado 80021/USA
<b>Signature of Inventor 202:</b> 				<b>Date:</b> 3-7-00

2	<b>Full Name Of Inventor</b>	<b>Family Name</b> Creager	<b>First Given Name</b> Robert	<b>Second Given Name</b> S
0	<b>Residence &amp; Citizenship</b>	<b>City</b> Berthoud	<b>State or Foreign Country</b> Colorado	<b>Country of Citizenship</b> USA
3	<b>Post Office Address</b>	<b>Post Office Address</b> P O Box 1318	<b>City</b> Berthoud	<b>State &amp; Zip Code/Country</b> Colorado 80513/USA
<b>Signature of Inventor 203:</b> 				<b>Date:</b> 3/15/00